

# METAL ROOFING SYSTEMS

## SMI 1.0" FF SnapLock Standing Seam

### Panel Information:

|                 |                            |
|-----------------|----------------------------|
| Panel Type:     | Standing Seam              |
| Panel Seam:     | SnapLock                   |
| Panel Width:    | 16"                        |
| Seam Height:    | 1.0"                       |
| Panel Material: | 22 GA - 24 GA Min          |
| Panel Surface:  | Smooth / Embossed Optional |
| Panel Clip:     | None                       |
| Minimum Slope:  | 3/12                       |
| Substrate:      | Plywood                    |



### Panel Testing:

|   |                        |
|---|------------------------|
| Uplift Resistance:                      | UL 90                  |
| Hail Rating:                            | Class 4 Impact UL 2218 |
| Fire Rating:                            | UL Class A             |
| Texas Department of Insurance Approval: | RC-560                 |

### Panel Notes:

- With this 24 GA, 16" wide panel, you may opt to use heavier gauge coil and narrower width panels. Fastener spacing will not change.
- This panel uses a 20" coil. Maximum width coil of 24".
- This panel uses 4-1/16" of material to form the panel.
- If you take the square footage of the roof and multiply that by 1.25, the total will be the amount coil needed to manufacture the panels.
- This panel is NOT approved for Weathertight Warranties.

