

ENGINEERED METAL ROOFING SYSTEMS

SMI 1.5" SnapLock 550 Standing Seam

Panel Information:

| | |
|-----------------|--|
| Panel Type: | Standing Seam |
| Panel Seam: | SnapLock |
| Panel Width: | 19" (Steel) / 15" (Aluminum) |
| Seam Height: | 1.5" |
| Panel Material: | 22 GA - 24 GA Min, .032 - .040 |
| Panel Surface: | Smooth / Embossed Optional |
| Panel Clip: | Required Per Engineering |
| Minimum Slope: | 2/12 |
| Substrate: | Plywood (Steel), Plywood, B-Deck, B-Deck with ISO (Aluminum) |



Panel Testing:

| | |
|---|------------------------|
| Uplift Resistance: | UL 580, UL 1897, UL 90 |
| Air Infiltration: | ASTM E 1680 |
| Water Penetration: | ASTM E 1646 |
| Hail Rating: | Class 4 Impact UL 2218 |
| Fire Rating: | UL Class A |
| Texas Department of Insurance Approval: | RC-396* |
| FBC Non-HVHZ Approval: | FL18316* |

Panel Notes:

- With this wide panel engineering, you may opt to use heavier gauge coil and narrower width panels. Clip spacing will not change.
- This panel uses a 24" coil (Steel) / 20" coil (Aluminum). Maximum width coil of 24".
- This panel uses 5-1/8" of material to form the panel.
- If you take the square footage of the roof and multiply that by 1.27, the total will be the amount of coil needed to manufacture the panels.
- This panel is approved for Weathertight Warranties.

* Available in steel only.

